



JF Series™ Round Body · Standard Head · Rubber Nut

AMERICAN STANDARD

RUBBER NUT

The RivetKing JF Series Rubber Nuts are used as a removable rivet nut. Installation is performed with the bolt or screw itself. To remove the rivet nut, just remove the bolt or screw. Rubnuts can also be used as vibration isolators to prevent the rattle and pullout. Typical applications are for the installation of mirrors or other hardware in utility trucks, compressors, and engines.



INCH
ALL DIMENSIONS
ARE IN INCHES

THREAD SIZE	PART CODE	GRIP CODE	GRIP RANGE MIN - MAX	L BODY LENGTH REF	B HEAD DIA REF	C HEAD HEIGHT REF	D BODY DIA REF	HOLE SIZE +.002/-0
6-32 UNC	JF-3100	1	.015 - .156	0.499	0.433	0.050	0.311	0.312
6-32 UNC	JF-3250	2	.375 - .511	0.981	0.551	0.035	0.240	0.250
8-32 UNC	JF-4100	1	.015 - .156	0.496	0.433	0.050	0.311	0.312
8-32 UNC	JF-4140	2	.015 - .172	0.560	0.750	0.060	0.311	0.312
10-32 UNF	JF-5150	1	.015 - .192	0.559	0.500	0.036	0.374	0.377
10-32 UNF	JF-5170	2	.035 - .232	0.669	0.562	0.040	0.374	0.377
10-32 UNF	JF-5190	3	.030 - .227	0.824	0.750	0.187	0.374	0.377
10-32 UNF	JF-5250	4	.300 - .600	1.040	0.551	0.051	0.374	0.503
1/4-20 UNC	JF-6200	1	.031 - .187	0.831	0.750	0.187	0.500	0.503
1/4-20 UNC	JF-6250	2	.250 - .457	1.051	0.641	0.078	0.500	0.503
5/16-18 UNC	JF-8200	1	.016 - .156	0.721	0.846	0.126	0.625	0.625
5/16-18 UNC	JF-8250	2	.156 - .375	1.100	0.846	0.225	0.625	0.625
3/8-16 UNC	JF-1027	1	.015 - .437	1.062	1.160	0.187	0.750	0.753

METRIC
ALL DIMENSIONS ARE IN
MILLIMETERS (MM)

THREAD SIZE	PART CODE	GRIP CODE	GRIP RANGE MIN - MAX	L BODY LENGTH REF	B HEAD DIA REF	C HEAD HEIGHT REF	D BODY DIA REF	HOLE SIZE +0.05/-0
M3-0.5	JF-3100M	1	0.40 - 4.00	12.60	11.00	1.20	7.90	7.90
M3-0.5	JF-3250M	2	9.50 - 15.40	24.90	14.00	0.90	6.10	6.10
M4-0.7	JF-4100M	1	0.40 - 4.00	12.60	11.00	1.20	7.90	7.90
M4-0.7	JF-4140M	2	0.40 - 4.40	14.20	19.05	1.50	7.90	7.90
M5-0.8	JF-5150M	1	0.40 - 4.90	14.10	12.70	0.90	9.60	9.60
M5-0.8	JF-5170M	2	0.85 - 5.90	17.00	14.00	1.00	9.60	9.60
M5-0.8	JF-5190M	3	0.80 - 5.80	20.95	18.95	4.40	9.60	9.60
M5-0.8	JF-5250M	4	7.90 - 15.00	26.50	14.00	1.30	9.60	9.60
M6-1.0	JF-6200M	1	0.80 - 4.70	21.10	19.05	4.75	12.70	12.70
M6-1.0	JF-6250M	2	6.40 - 11.50	26.70	16.30	2.00	12.70	12.70
M8-1.25	JF-8200M	1	0.40 - 4.00	18.30	21.50	3.20	15.90	15.90
M8-1.25	JF-8250M	2	3.95 - 9.50	27.90	21.50	5.70	15.90	15.90
M10-1.5	JF-1027M	1	0.38 - 11.10	27.00	29.50	4.75	19.05	19.05

THE PART NUMBER IS COMPLETE BY ADDING THE MATERIAL AND FINISH CODES AS A SUFFIX TO THE PART CODE:

MATERIAL/FINISH CODES:

NO SUFFIX = Brass/EPDM
BE = Brass/EPDM

3N = Stainless/Neoprene
3E = Stainless/EPDM

EXAMPLE:

Part Code JF-3100 in
Brass/Neoprene is... JF-3100BN